

AURUM

Hopper Elevators



AURUM PACKAGING SYSTEMS PVT. LTD.

Office: 101, Shivneri, Near Gamdevi Maidan, Naupada, Thane-400602. INDIA

Phone: (91-22) 25415807, Fax: (91-22) 25425782.

E-mail: sales@aurumpackaging.com Website: www.aurumpackaging.com

HOPPER ELEVATOR

TECHNICAL SPECIFICATIONS:

☞	Principle of Operation	Mechanical / Pneumatic	
☞	Product	Package Material Shape	Flats, Tins, Jars, Pots, Tubs, Bottles Plastic / Tin Round/Rectangular/Square/Oval
☞	Output	To suit application	
☞	Electrical Power	1.5 KW, 440 VAC, 3 Phase, 50 Hz	
☞	Hopper Capacity	250 / 320 / 500 / 1000 / 3000 Litres	
☞	Release Height	To suit application	

SALIENT FEATURES:

- ☞ Hopper Elevator (Pneumatic) can be placed away from main packaging line to avoid hindrance to man / material movement.
- ☞ Output can be distributed into two Unscramblers.
- ☞ Auto Start / Stop depending upon Unscrambler level.

OPTIONAL FEATURES

- ☞ Hopper empty alarm