

AURUM

Unscramblers



AURUM PACKAGING SYSTEMS PVT. LTD.

Office: 101, Shivneri, Near Gamdevi Maidan, Naupada, Thane-400602. INDIA

Phone: (91-22) 25415807, Fax: (91-22) 25425782.

E-mail: sales@aurumpackaging.com Website: www.aurumpackaging.com

UNSCRAMBLER

TECHNICAL SPECIFICATIONS:

☞	Principle of Operation	Gravity / Pneumatic	
☞	Product	Package Material Shape	Flats, Tins, Jars, Pots, Tubs, Bottles Plastic / Tin Round/Rectangular/Square/ Oval
☞	Output Speed	Gravity Unscrambler Pneumatic Unscrambler	Upto 1000 Units / Min Upto 300 Units / Min
☞	Electrical Power	1.5 KW, 440 VAC, 3 Phase, 50 Hz	
☞	Compressed Air	To suit Application	
☞	Overall Dimensions	Gravity Unscrambler Pneumatic Unscrambler	1. 8 M (L) x 1.1 M (W) x 2.8 M (H) 0.8/1.0/1.2/1.5/1.8/2.0 M Bowl Dia

SALIENT FEATURES:

- ☞ PLC Controlled Operation
 - ☞ Output in multi-rows for Gravity Unscrambler
 - ☞ VFD for machine speed control
 - ☞ Contact parts in S.S. / PVC / Nylon
 - ☞ Available in Clockwise / Anticlockwise configuration
 - ☞ Level Sensor to start-stop Unscrambler automatically
 - ☞ Level Sensor to start-stop Hopper Elevator automatically
-

OPTIONAL FEATURES

☞	Hopper Elevator	Pneumatic / Mechanical Hopper Capacity Hopper Empty Alarm	250 / 320 / 500 / 1000 / 3000 Lit.
☞	Orientator	Linear Rotary Detection	Servo Controlled, Single row Pneumatic, 6 - 12 Heads Sensor / Camera / Vision System
☞	Release in pucks		
☞	Combination of two or more Unscramblers to achieve higher outputs.		

Please consult AURUM for special applications

(We reserve the right to change the specifications without notice)