



Sleeve Applicator (Label)

Sleeve label applicator designed for automatically inserting heat shrinkable decorative PVC/ PET sleeves on containers / bottles at speeds up to 300 upm. Sleeve labelling provides a 360 degree high quality decoration on containers or bottles.

Technical Specifications:

■ Product	Bottle Diameter Bottle Height Sleeving Dia Material Shape	40 – 100 mm 100 – 350 mm 40 – 100 mm Plastic / Metal / Glass Round
■ Sleeve	Lay Flat Width Height Thickness Material	65 – 165 mm 100 – 300 mm 40 – 75 microns Heat Shrinkable PVC / PET
■ Sleeve Roll	Diameter Core Diameter Output	Upto 600 mm 254 mm (10") Upto 300 UPM
■ Electric Power	440 VAC, 3 Phase, 50 Hz, 3 KW	
■ Dimensions	3.5 M (L) x 2.2 M (D) x 2.6 M (H)	



Salient Features :

- Includes Sleeve Applicator, Conveyor, Product Separation Device and Controls.
- VFD for Conveyor and Machine Speed Control.
- Registration Mark Sensor arrangement.
- Servo Controlled Film Feeding.
- PLC Controlled Operation.
- No Bottle , No Sleeve Interlock.
- Operator Interface Panel.
- Unwinder for Smooth Film Feeding.
- Quick Changeover / Few Change Parts.

Optional Features

- Steam Tunnel / Shrink Tunnel
- Pre – Heating Tunnels



(We reserve the right to change the specifications without notice)

AURUM

AURUM PACKAGING SYSTEMS PVT. LTD.

702/A, C, 7th WIFI Park, IT Premises Co-Op. Soc. Ltd., Opp. Aplab Industries,
Wagle Industrial Estate, Thane-400604. Maharashtra, India.
Tel.: (91-22) 25415807 / 25827768 | E-mail: sales@aurumpackaging.com

Member company of :  **Technoshell**
Automations Pvt. Ltd.
www.technoshell.com